

# LIFT WITH EASE

Efficient and ergonomic  
material handling





Item no.: Vertical MV

## Vertical MV



























Weight (kg)	12, 13, 18, 7, 8, 9, 9.2
Maximum capacity (kg)	100, 20, 40, 50, 55, 65
Stroke length (mm)	1200, 1500, 1800, 2100, 2400, 2700, 3000, 600, 900
Bal-Trol model	MV
Configuration height (mm)	-995

The Vertical MV is a flexible standard model in the Bal-Trol range and is suitable for environments where a compact design needs to be combined with broad versatility. It is a natural choice when space is limited but not as critical as it is for the mini models. The model features unlimited rotation via an air swivel at the top, providing excellent freedom of movement and smooth handling in daily operations. The simple mounting with just a single mounting eye makes the solution easy to integrate into various environments with overhead crane systems or cranes. The Vertical MV handles loads between 20 and 100 kilograms and is available with stroke lengths from 600 to 3000 millimeters.

A versatile Bal-Trol for work environments where flexibility and easy integration are prioritized.

## Versions

	Article number	Weight (kg)	Maximum capacity (kg)	Stroke length (mm)	Bal-Trol model	Configuration height (mm)
	90-10589	7	40	2100	Etc.	
	90-10584		40	2100	Etc.	995
	90-10583	9-2	40	1500	Etc.	
	90-10581		50	900	Etc.	
	90-10580	8	55	1500	Etc.	
	90-10577	12	100	1800	Etc.	
	90-10576		100	600	Etc.	
	90-10309		50	2100	Etc.	
	90-10570		65	1200	Etc.	
	90-10307		50	1500	Etc.	
	90-10303	8	65	2400	Etc.	
	90-10328	12	100	1800	Etc.	
	90-10560		65	1500	Etc.	
	90-10558	13	100	1500	Etc.	
	90-10285		40	2700	Etc.	
	90-10280		40	600	Etc.	
	90-10302	9	65	2100	Etc.	
	90-10284		40	2100	Etc.	
	90-10529		65	3000	Etc.	
	90-10528		20	1500	Etc.	
	90-10524	18	100	1500	Etc.	
	90-10304		65	2700	Etc.	
	90-10329		100	2100	Etc.	
	90-10281		40	1200	Etc.	



## **CONTACT US**

### **USA**

Lifts All Inc.  
728 William Blount Dr,  
Maryville, TN 37801  
USA  
E-mail: [info@liftsall.us](mailto:info@liftsall.us)  
Telephone: +1 865-324-2014  
Website: [liftsall.com](http://liftsall.com)

### **HEAD OFFICE WORLDWIDE**

Lifts All AB  
Passadvägen 10  
176 67 Järfälla  
Sverige  
E-mail: [lifting@liftsall.se](mailto:lifting@liftsall.se)  
Telephone: 08-754 90 15  
Website: [liftsall.com](http://liftsall.com)